

Face Length	MM	60.6
Face Width	MM	37.8
Height	MM	8.8
Pin Spacing	MM	2.54
Row SPacing	MM	45.72
No. of pins	Pins	14

(2.54 x 6 = 15.24)

Note : All Dimensions are in mm Tolerance ± 0.2 mm

PART NO.	Column Anode	CA	KLP2088 I	KLP2088 SR	KLP2088 G	KLP2088 SG	KLP2088 SY	KLP2088 SA	KLP2088 UR	KLP2088 SO	KLP2088 B/UB	KLP2088 BG	KLP2088 UG	KLP2088 W		
	Column Cathode	CC	KLP2188 I	KLP2188 SR	KLP2188 G	KLP2188 SG	KLP2188 SY	KLP2188 SA	KLP2188 UR	KLP2188 SO	KLP2188 B/UB	KLP2188 BG	KLP2188 UG	KLP2188 W		
OPERATING CHARACTERISTICS AT 25°C (Bigger Display may have more than one LED chip per segment)			UNITS	SYMBOL	IRED I	SUPER RED SR	GREEN G	SUPER GREEN SG	SUPER YELLOW SY	SUPER AMBER SA	ULTRA RED UR	SUPER ORANGE SO	BLUE B/UB	BLUE GREEN BG	ULTRA GREEN UG	WHITE W
Semiconductor Composition					AlGaAs		GaP/AlInGaP		AlInGaP			SiC / GaInN				
Forward Voltage - Typical @ 10mA			V	V _F	2.10	1.90	2.20	2.20	2.10	2.10	1.90	1.90	3.50	3.50	3.50	3.50
Forward Voltage - Maximum @ 20 mA			V	V _{FM}	2.40	2.10	2.60	2.40	2.40	2.40	2.10	2.40	4.50	4.50	4.50	4.50
Reverse Current @ V _R = 5V			μA	I _R	100	100	100	100	100	100	100	100	100	100	100	100
Peak Emission Wavelength			nm	λ _p	630	660	568	568	590	610	645	620	470	502	525	---
Emission Wavelength Half Width			nm	Δλ	35	20	30	15	15	15	20	20	25	30	35	---
Luminous Intensity per Segment			μcd	I _v	3500	6000	4000	6000	7000	7500	13000	13000	6000	7000	17000	---
ABSOLUTE MAXIMUM RATINGS AT 25°C			V	V _R	5	5	5	5	5	5	5	5	5	5	5	5
Reverse Voltage			mA	I _F	20	20	20	20	20	20	20	20	20	20	20	20
Forward Current (avg)			mA	I _{FS}	80	80	80	80	80	80	80	80	80	80	80	80
Peak Forward Current (T<1μs)																
Operating / Storage Temperature Range			-10° C to + 85° C													
Lead Soldering Temperature			< 260° C for 5 Seconds													
Series Resistor to be used per segment : 300 Ohms @ 5V Supply (OR) 50 to 100 Ohms @ 3V Supply																

ELECTRICAL CHARACTERISTIC CURVES

